

LED SURFACE PANEL LIGHT

Ultra-Slim Design, Unmatched Brightness

Model No.	Watt	Lumens	Height	Outer Dia (in mm)	Shape
RNSPL4	4 W	480	35MM	80 x 80	ROUND & SQUARE
RNSPL9	9 W	1080	32MM	100 x 100	ROUND & SQUARE
RNSPL12	12 W	1440	32MM	135 x 135	ROUND & SQUARE
RNSPL15	15 W	1800	32MM	135 x 135	ROUND & SQUARE
RNSPL22	22 W	2640	32MM	195 x195	ROUND & SQUARE

Available Color Temperature (CCT) :

3000K (Warm White), 4000K (Natural White), 6500K (Cool White)

Technical Specification : -

Input Voltage :

110Vac- 270Vac / 50Hz-60Hz

Beam Angle : 140 Degree



CRI (Color Rendering Index) : 80

Surge Protection : 2Kv Inbuilt

Power Factor : >0.90

THD : <10%

Housing Material : Powder Coated Non- Corrosive Aluminum Die-Cast

LED Source : 0.2Watt Higher Lumen LM80 CertifiedLED
(CREE/Bridglux/Edision/Seoul)

Short Circuit & Open Circuit Protection / Built-In PFC Function

440Vac Input Voltage Protection / Under Voltage & Over Voltage Protection



CLICK TO CONNECT



24 Months
Warranty



BIS Approved
LED Driver



Made in India



Premium
Products